

Jet2-I, Jet8-I

Ion Spot Dryer



Overview

Compact washdown blower housing with an integrated high-speed jet blower. Direct flow of ionized air from the blower outlet to the target surface eliminates plumbing efficiency losses, simplifies maintenance and accelerates installation.

Jet2-I and Jet8-I combine high-velocity air with ionizing points so dust and process residue release from charged surfaces. Two or eight ion nozzles sit in line on the housing. Includes Ion High-Voltage supply and wire (8 m). Warning labels mark the ionizing zone.

Mounting options include a floor tripod, a Ø30 mm or twin Ø12 mm tube conveyor sidewall brackets, M8 connections in the end caps and M6 taps on the housing.

- IDEAL FOR
CPG, De-Static Cleaning, Printing
- INDUSTRIES
CPG
- COMPRESSED AIR REPLACEMENT
94% kW Savings, Plug-n-Play
- IMPROVE QUALITY
Enhance Drying, Remove static adhered debris, Improve Up-time
- SMART
Safety, Low Maint., Smallest Footprint

Technical specifications

Parameter	Jet2-I	Jet8-I
Nozzle architecture	Dual inline ionizing chevron Ø10 mm / 0.375 in nozzles; 8 m HV wire connected; Tungsten ion points	
Ion nozzles	2	8
Rated voltage	230 VAC	
Rated current	2.6 A	10.4 A
Power consumption	528 W	2 112 W
Max. air pressure	25 kPa	
Max. air flow	1 500 L/min	6 000 L/min
Life / sound / temp.	25 000 h · 72 dBA · -20 °C to +50 °C	
Electrical enclosure type/size	SS 40 × 30 × 20 cm	SS 60 × 40 × 20 cm
Mounting options	Tripod / Ø30 mm tube conveyor sidewall bracket / Ø12 mm tube conveyor sidewall bracket pair	
Origin / standards / warranty	Germany / UL 508A, IEC 60204-1 / Wash-down / 3 years extended	

Dimensions

