

Jet2-C Electrical Panel Spot Cooler

Targeted forced air cooling inside Electrical Panel



Overview

Compact washdown blower housing with an integrated high-speed jet blower. The blower mounts through the panel wall so cooling air is aimed at hot spots — drives, PLCs, power supplies — without adding a full cabinet air conditioner.

Jet2-C uses two flexible segmented spider arms with chevron Ø10 mm / 0.375 in outlets. Arms bend independently so airflow can be pointed at the components that run hottest. A gasketed flange and filtered exhaust keep the enclosure sealed and vented.

Cut-out and M6 flange dimensions are shown on the drawing. The remote controller mounts on the backplane. Installation requires two panel cut-outs for the blower assembly and vent, plus controller mounting and a 24 VDC connection.

Customer must determine if additional forced-air cooling at 25 kPa / 1 500 L/min is sufficient for cooling needs.

- IDEAL FOR**
Panel Builders
- INDUSTRIES**
Industrial, OEMs
- COMPRESSED AIR REPLACEMENT**
94% kW Savings, Plug-n-Play
- IMPROVE QUALITY**
Enhance Cooling, Prevent Thermal Overloads
- SMART**
Safety, Low Maint., Smallest Footprint

Technical specifications

Parameter	Jet2-C
Nozzle architecture	Flexible segmented spider arms, chevron Ø10 mm / 0.375 in
Nozzles	2
Rated voltage	24 VDC
Rated current	22 A
Power consumption	528 W
Max. air pressure	25 kPa
Max. air flow	1 500 L/min
Life / sound / temp.	25 000 h · 72 dBA · -20 °C to +50 °C
Panel interface	Gasketed M6 flange, 111 × 34 mm enclosure cut-out
Controller	Remote backplane-mount drive included, W 35 mm × L 118 mm × H 76 mm
Vent / Filter	106 × 106 × 10 mm external / cut-out 82 × 82 mm / M5 fastener centers 91 × 91 mm, included
Origin / standards / warranty	Germany / UL 508A, IEC 60204-1 / 3 years extended

Dimensions

